

In-Line Dual TDS Monitor

Measure the tap water TDS level coming in vs. the purified water TDS level going out of your Reverse Osmosis water filtration system at any time.

FEATURES

- Displays TDS levels of the feed water and product water with in & out electrode probes.
- Highly efficient and accurate due to its advanced microprocessor technology.
- Auto-Off function conserves battery power. The unit shuts off automatically after 10 minutes of non-use.
- Dual Range 0-9990 ppm (From 0 - 999 ppm the resolution is 1 ppm. From 1000 to 9990 ppm, the resolution is 10 ppm, indicated by a blinking 'x10' image.)
- Factory Calibrated: our meters are calibrated with a 342 ppm NaCl solution. Meters can be recalibrated with a mini-screwdriver.
- Comes equipped with Mur-lok® Quick-Connect T-fittings (1/4" or 3/8").
- Installs quickly and easily.

SPECIFICATIONS

Range: 0-9990 ppm

Accuracy: ±2%

Cable Length: 24.5" (including sensor)

Fittings: 1/4" standard, also available with 3/8"

Power source: 2 x 1.5V button cell batteries (included)

Battery life: approx. 1000 hours of continuous use

Size: 7.6 x 2 x 4.7 cm (3 x .8 x 1.9 in.)

Weight: 79.4 g (2.8 oz.)



Taste the Difference!

37 Bell Crescent, Westlake Business Park, Tokai
Suite 220, Postnet X18, Rondebosch, 7700
Tel: +27 21 702 3262 Fax: +27 21 702 3270
Customer Care: 0800 4 WATER
Website: www.h2o.co.za E-mail: info@h2o.co.za

H2O International SA (PTY) LTD Registration number : 2003/002835/07